

### C33 REFLEX



<b>Certification</b>	EN 361 (full body harness) <b>CE 2756</b>	
<b>Webbing</b>	Compact 30 (BL > 30 kN)	
<b>Buckles</b>	<b>Classic</b> (Steel) 	<b>Classic-Automatic</b> click type (Steel) 
<b>Rings</b>	Frontal ring: Forged 40 (Steel, BL > 40 kN) Dorsal ring: Welded 25 (Steel, BL > 25 kN)	
<b>Optional accessories</b>	Plastic rings; Use: lanyard parking / tool parking (Max. 2 kg) 	
<b>Available sizes</b>	● S-M ● L-XL ● XXL-XXXL	
<b>Max. 150 kg</b>	In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 kN. (Max. 150 kg : user + equipment). <b>Please follow using instruction manual!</b>	
<b>Up to 10 years</b>	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. <b>Please follow using instruction manual!</b>	