

### FAST

Adjustable lanyard for work positioning or restraint



<b>Certification</b>	EN 358:2018 (Adjustable lanyard for work positioning or restraint) <b>CE 2233</b>																									
<b>Max. 150 kg</b>	Allowed user weight: Max. 150 kg (user+equipment) BEFORE USE READ THE INSTRUCTIONS CAREFULLY !																									
<b>Rope</b>	Type: kernmantle rope certified acc. to EN 1891 type A; Material: polyamide; Diameter: Ø 14 mm;																									
<b>Ends</b>	<u>Sewn ends</u> + transparent protective sleeve;																									
<b>Ropegrab</b>	Type: cam type ropegrab; Material: aluminium alloy (anodized);																									
<b>Length</b>	<ul style="list-style-type: none"> <li>▪ 1,5 m (Art. No. 12-1044-51-01-50)</li> <li>▪ 2 m (Art. No. 12-1044-51-02-00 )</li> </ul> <i>*other lengths on request</i>																									
	<ul style="list-style-type: none"> <li>▪ certified according to EN 362 (customer's choice): Carabiners shown in the photo:</li> </ul> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th></th> <th><b>AIKO (624)</b> <i>left</i></th> <th><b>QUADRO (232)</b> <i>right</i></th> </tr> </thead> <tbody> <tr> <td><b>Certif.</b></td> <td><b>EN 362:2004/B</b></td> <td><b>EN 362:2004/T</b></td> </tr> <tr> <td></td> <td>Aluminium alloy</td> <td>Aluminium alloy</td> </tr> <tr> <td></td> <td>22 kN</td> <td>40 kN</td> </tr> <tr> <td></td> <td>Tri Lock</td> <td>Auto Lock</td> </tr> <tr> <td></td> <td>86 g</td> <td>126 g</td> </tr> <tr> <td></td> <td>20 mm</td> <td>25 mm</td> </tr> <tr> <td></td> <td>110/61 mm</td> <td>141/79 mm</td> </tr> </tbody> </table>			<b>AIKO (624)</b> <i>left</i>	<b>QUADRO (232)</b> <i>right</i>	<b>Certif.</b>	<b>EN 362:2004/B</b>	<b>EN 362:2004/T</b>		Aluminium alloy	Aluminium alloy		22 kN	40 kN		Tri Lock	Auto Lock		86 g	126 g		20 mm	25 mm		110/61 mm	141/79 mm
	<b>AIKO (624)</b> <i>left</i>	<b>QUADRO (232)</b> <i>right</i>																								
<b>Certif.</b>	<b>EN 362:2004/B</b>	<b>EN 362:2004/T</b>																								
	Aluminium alloy	Aluminium alloy																								
	22 kN	40 kN																								
	Tri Lock	Auto Lock																								
	86 g	126 g																								
	20 mm	25 mm																								
	110/61 mm	141/79 mm																								