




















FLEXIBLE 12 / FLEXIBLE 14

Adjustable positioning and restraint lanyard



Certification	EN 358:2018 (work positioning / restraint lanyards) CE 2233														
Max. 150 kg	Allowed weight: Max. 150 kg (user + equipment)  BEFORE USE, CAREFULLY READ THE INSTRUCTIONS!														
Rope	Type: kernmantle rope certified acc. to EN 1891 type A; Material: polyamide; Diameter: Ø 12 mm (FLEXIBLE 12); Ø 14 mm (FLEXIBLE 14);														
Ends	<u>Sewn ends</u> + protective sleeve (transparent);														
Adjuster	Aluminium H type buckle														
Lenght	<ul style="list-style-type: none"> ▪ 1,5 m ▪ 2 m <i>*other lengths on request</i>														
	<ul style="list-style-type: none"> ▪ certified according to EN 362 (customer's choice): <p><i>Carabiners shown in the photo: 2x KANGRI (022)</i></p> <table border="1"> <tr> <td>Certif.</td> <td>EN 362:2004/T</td> </tr> <tr> <td></td> <td>Steel</td> </tr> <tr> <td></td> <td>25 kN</td> </tr> <tr> <td></td> <td>Auto Lock</td> </tr> <tr> <td></td> <td>238 g</td> </tr> <tr> <td></td> <td>18 mm</td> </tr> <tr> <td></td> <td>130/68 mm</td> </tr> </table>	Certif.	EN 362:2004/T		Steel		25 kN		Auto Lock		238 g		18 mm		130/68 mm
Certif.	EN 362:2004/T														
	Steel														
	25 kN														
	Auto Lock														
	238 g														
	18 mm														
	130/68 mm														