









Anchor device / Connecting lanyard

HARDY 3	HARDY 3R	HARDY NX	HARDY NXR
			
3 pers. 	3 pers. 	3 pers. 	3 pers. 
Ø 8mm steel wire rope (zinc plated) BL > 35 kN	Ø 8mm steel wire rope (zinc plated) BL > 35 kN	Ø 8mm stainless steel wire rope BL > 30 kN	Ø 8mm stainless steel wire rope BL > 30 kN

*BL = breaking load [kN]

Certifications	EN 354:2010 – Connecting lanyard (MAX. 2m) EN 795:2012 – Anchor device (type B) CEN/TS 16415:2013 Recommendations for anchor devices for use by more than one person simultaneously <u>Max. 3 persons</u>		CE 2756
Materials	HARDY 3 and HARDY 3R Cable: zinc plated steel Ferrules: aluminum alloy Thimbles: zinc plated steel Ring: zinc plated steel	HARDY NX and HARDY NXR Cable: stainless steel Ferrules: stainless steel Thimbles : stainless steel Ring: stainless steel	
Weight	HARDY 3 (L = 1m) 480 g (+320 g / linear meter added) HARDY NX L = 1m 480 g (+320 g / linear meter added) HARDY 3R (L = 1m) 614 g (+320 g / linear meter added) HARDY NXR (L = 1m) 618 g (+320 g / linear meter added)		