

Datasheet

KOALA & KOALA PLUS

KOALA – positioning belt; KOALA PLUS – positioning belt + positioning lanyard (non-removble);







Certification	EN 358:2018 (belts and lanyards for work positioning or restraint) C € 2756		
Webbing	Material: PES fibers (black); Width: 85mm;		
Buckles	Dual locking system:		
Rings	Positioning rings: (aluminium, BL > 25 kN);		
	Standard length: 1,5 m (Max.); *lengths up to 2 m on request; Rope: Ø14 mm, Kernmantle type; Length adjuster: aluminium; Connector: EN 362/T certified		
	Connector specifications: 022 KANGRI		
Positioning lanyard		Steel	
•		25 kN	

	Connector. EN 302/1 Certified		
	Connector specifications: 022 KANGRI		
Positioning lanyard		Steel	
(KOALA +)		25 kN	
(NOALA)	→	Auto Lock	
	9	238 g	
		18 mm	
		130/68 mm	
Sizes	S-M (80-90cm); M-L (90-100cm); L-XL (100-110cm); XL-XXL (110-120cm);		
Max. 150 kg	KOALA and KOALA PLUS are tested and approved for users up to 150kg! (Max. 150 kg: user + equipment). Please follow using instruction manual!		
Up to	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in		

	Please follow using instruction manual!
	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greasses or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!
ı	

10 years