

Low stretch kernmantle ropes according to EN 1891 tip A

CE 0408

			
FIDES III 10,5	PATRON PLUS 10,5	PATRON 12	PATRON 14
Diameter: 10,5 mm Core & Mantle: Polyamide Certified: EN 1891 type A Weight: 74 gr/m BL (direct): >2800 daN BL (8-er knot): >1800 daN BL (sewed eye): >2200 daN Elongation: 4 % <i>BL = Breaking Load</i>	Diameter: 10,5 mm Core & Mantle: Polyamide Certified: EN 1891 type A Weight: 72 gr/m BL (direct): >3200 daN BL (8-er knot): >1800 daN BL (sewed eye): >2200 daN Elongation: 3 % <i>BL = Breaking Load</i>	Diameter: 12 mm Core & Mantle: Polyamide Certified: EN 1891 type A Weight: 92 gr/m BL (direct): >3800 daN BL (8-er knot): >2200 daN BL (sewed eye): >2900 daN Elongation : 3 % <i>BL = Breaking Load</i>	Diameter: 14 mm Core & Mantle: Polyamide Certified: EN 1891 type A Weight: 100 gr/m BL (direct): >4000 daN BL (8-er knot): >2200 daN BL (sewed eye): >3000 daN Elongation : 3 % <i>BL = Breaking Load</i>