



V33 ADVENTURE

 <p style="text-align: center;">Evo Power&Comfort</p>	<p>Certification EN 361 (full body harness) CE 2756</p>
 <p style="text-align: center;">Classic (Classic-Automatic) Automatic</p>	<p>Webbing Evo: S-Guard Teflon (treatment: TEFLON[®]); Power&comfort: Platinum Safety Reflex; Automatic: Vertiqua Standard 33 Hi-Viz (BL > 3300 daN); Classic: Vertiqua Standard 33 (BL > 3300 daN); Classic-Automatic: Vertiqua Standard 33 (BL > 3300 daN);</p>
<p>Buckles Evo: COBRA[®] Pro-Style (click-lock type); Power&comfort: AUTOMATIC PREMIUM (click-lock type); Automatic: SMART-LOCK (click-lock type); Classic: CLASSIC (simple, with two coupling plates); Classic-Automatic: CLASSIC-Automatic (click-lock type);</p>	<p>Rings Evo: SPACE AERO 7 (Aluminium, BL > 3000 daN); Power&comfort: ANSI STEEL (steel); Automatic: Forged 40 (steel); Classic: Forged 40 (steel); Classic-Automatic: Forged 40 (steel);</p>
<p>Sizes available</p> <ul style="list-style-type: none"> • S-M • M-L • L-XL • XXL-XXXL 	<p>Max. 150 kg</p> <p>In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 KN. (Max. 150 kg : user + equipment). Please follow using instruction manual!</p>
<p>Up to 10 years</p> <p>Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!</p>	