

Datasheet

V33 PHARMA



	EN 261 (full body borness)
Certification	EN 361 (full body harness) EN 1497 (rescue harness)
	€€ 2756
Webbing	Webbing: PERFORMANCE XP;
	Special treatments:
	• Nanodirt [®] (prevents impregnation with dirt and oils);
	 Ag⁺ ions; (has anti-microbial and fungicide action);
Buckles	Buckles: high tensile steel + plastic insulation
	(overmolded with nylon);
	BL > 1780 daN;
Rings	Rings: high tensile steel + plastic insulation
	(overmolded with nylon); BL > 2200 daN;
	,
Available sizes	 S-M M-L
	• M-L • L-XL
	L-AL XXL-XXXL
Max. 140 kg	In this case, a suitable energy absorbing lanyard has
	to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 KN.
	(Max. 140 kg : user + equipment)
	Please follow using instruction manual!
	Safety harnesses belonging to a single user, which
Up to 10 years	were subject to periodical inspections by experts and
	recorded in the Inspection Log, carefully treated and
	maintained, were stored in accordance with regulations, were not in contact with oils, greasses or
	aggressive chemicals, were not used extensively, can
	be hold in service for up to 10 years. Please follow
	using instruction manual!

V33 PHARMA