

V34 EXPLORER AC V34 EXPLORER OFFSHORE



V34 EXPLORER AC



V34 EXPLORER OFFSHORE

Certification	EN 361:2002 (full body harness) CE 2233
Webbing	V34 EXPLORER AC: Vertiqual Standard 33; V34 EXPLORER OFFSHORE: Vertiqual Standard 33;
Buckles	V34 EXPLORER AC: - steel adjusters (zinc plated + EDC paint); - ANSI Cobra® (aluminium alloy);  V34 EXPLORER OFFSHORE: - 316 stainless steel adjusters; - Cobra® NAUTIC(stainless steel); 
Rings	V34 EXPLORER AC: SPACE AERO 7 (aluminum alloy); V34 EXPLORER OFFSHORE: 316 stainless steel;
Sizes available	S-M , M-L , L-XL , XXL-XXXL
Max. 150 kg	In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 kN. (Max. 150 kg : user + equipment). Please follow using the instruction manual!
Up to 10 years	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!