

Datasheet

V83 STRATOSPHERE



Automatic

Certification	EN 361 (Full Body Harness) EN 358 (Positioning Belt)
	EN 813 (Sit Harness)
	C€ 2756
Webbing	Classic: Vertiqual Standard 33;
	Automatic: Vertiqual Standard 33 Hi-viz;
	Power & Comfort: Platinum Safety Reflex; Evo: S-Guard TEFLON®;
Buckles	Classic: CLASSIC;
	Automatic: SMART-LOCK;
	Power & Comfort: AUTOMATIC-PREMIUM.
	Evo: COBRA® PRO-STYLE;



Rings	Classic: Aluminum; (B.L. > 30 kN) Automatic: Aluminum; (B.L. > 30 kN) Power & Comfort: ANSI STEEL (ANSI Z359.12); Evo: SPACE AERO 7 (Alu); (B.L. > 30 kN)
Available sizes	S-M; M-L; L-XL; XXL-XXXL
Max. 150 kg	In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 KN. (Max. 150 kg: user + equipment) Please follow using instruction manual!
Up to 10 years	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greasses or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!