

V85 ECLIPSE



Certification	EN 361:2002 (Full Body Harness) EN 358:2018 (Positioning Belt) EN 813:2024 (Sit Harness)			CE 2756
Webbing	Vertiqual Standard 33 (Width: 45mm; Material: PES;)			
Buckles	 Leg straps Quick-Lock Material: aluminium alloy (anodized); Width: 45 – 30mm (asymmetric);	 Shoulder strap Spring loaded adjuster Material: aluminium alloy (anodized); Width: 45mm;	 Waist belt / Back straps Material: high tensile steel (coated); Width: 45mm;	
	Rings	 Sternal / ventral ring SPACE AERO 7 Material: aluminium alloy (anodized);	 Positioning rings Forged 30 Material: high tensile steel (coated);	
Sizes	S-M , M-L , L-XL , XXL-XXXL			
Max. 150 kg	In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 KN. (Max. 150 kg : user + equipment) Please follow using instruction manual!			
Up to 10 years	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!			