













### Vertiline UNIVERSAL HEAVY 214



Certification	<b>EN 353-2:2002</b> (Guided type fall arresters including a flexible anchor line) <b>CE 2233</b>			
Rope	Type: Kernmantle rope; Diameter: Ø 14 mm ; Material (core and cover): polyamide fibers;			
Fall arrester device	Type: cam locking type; Detachable: YES; Material: zinc plated steel;			
Rope lengths / other lengths on request	12-0214-00-05-00 (5 m) 12-0214-00-10-00 (10 m) 12-0214-00-15-00 (15 m) 12-0214-00-20-00 (20 m) 12-0214-00-25-00 (25 m) 12-0214-00-30-00 (30 m) 12-0214-00-40-00 (40 m) 12-0214-00-50-00 (50 m)			
Energy Absorber	Type: 45mm tear-webbing; Performance: <b>acc. to EN 355</b> ; Suitable for users: <b>50 - 150 kg (fully equipped)</b> ( READ INSTRUCTIONS MANUAL FIRST! 📖 )			
Hooks /other, customer's choice	<i>*photo: COLORADO</i> (on the rope end)			
	<i>*photo: BLACKBURN</i> (on the absorber end)			
		Steel		Aluminium
		45 kN		28 kN
		Tri-Lock		Tri Lock
		314 g		109 g
		20 mm		22 mm
	139/77 mm		140/79 mm	