

Vertiline *UNIVERSAL HEAVY* 214



Zertifizierung	EN 353-2:2002 (Auffanggeräte an beweglicher Führung) CE 2233	
Seil	Typ: Kernmantel Seil; Diameter: Ø 14 mm ; Material: Polyamid;	
Seilklemme	Typ: Nockenklemme; Abnehmbar: JA; Material: Gezinktes Stahl;	
Längen / andere Längen auf Anfrage	12-0214-00-05-00 (5 m) 12-0214-00-10-00 (10 m) 12-0214-00-15-00 (15 m) 12-0214-00-20-00 (20 m) 12-0214-00-25-00 (25 m) 12-0214-00-30-00 (30 m) 12-0214-00-40-00 (40 m) 12-0214-00-50-00 (50 m)	
Bandfalldämpfer	Zertifizierung: EN 355 ; Für Benutzer: 50 - 150 kg (Benutzer+equipment) (Bitte Bedienungsanleitung beachten! ⓘ)	
Karabiner /andere auf Anfrage	*im Bild: COLORADO (aufs Seil)	*im Bild: BLACKBURN (auf dem BFD)
	 Stahl	 Aluminium
	 45 kN	 28 kN
	 Tri-Lock	 Tri Lock
	 314 g	 109 g
	 20 mm	 22 mm
	 139/77 mm	 140/79 mm