

Vertiline **UNIVERSAL HEAVY 214**



Certificare	EN 353-2:2002 (Opritor de cădere pe suport flexibil) CE 2233			
Coardă	Tip: Kernmantle; Diametru: Ø 14 mm ; Material (miez și înveliș): fibre poliamidice;			
Mecanism opritor	Tip: opritor cu camă; Detașabil: DA; Material: Oțel zincat;			
Lungimi disponibile / alte lungimi la cerere	12-0214-00-05-00 (5 m) 12-0214-00-10-00 (10 m) 12-0214-00-15-00 (15 m) 12-0214-00-20-00 (20 m) 12-0214-00-25-00 (25 m) 12-0214-00-30-00 (30 m) 12-0214-00-40-00 (40 m) 12-0214-00-50-00 (50 m)			
Absorbitor de energie	Tip: chingă 45mm, țesută; Performanțe: cf. EN 355; Pentru utilizatori: 50 - 150 kg (complet echipați) (ÎNAINTE DE UTILIZARE CITIȚI CU ATENȚIE INSTRUCȚIUNILE ! 📖)			
Carabiniere /altele, la alegere	*în imagine: COLORADO (pe coardă)		*în imagine: BLACKBURN (pe absorbitor)	
		Oțel		Aluminiu
		45 kN		28 kN
		Tri-Lock		Tri Lock
		314 g		109 g
		20 mm		22 mm
		139/77 mm		140/79 mm